



6 st skruvor 05-04-176 pos. 11 och 1 st packning 01-45284 samt 1 st packning 01-45410 pos. 13 levereras separat att användas för Pump II.  
 6 pcs screw pos. 11 and 1 + 1 pcs gasket pos 13 will be delivered separately to be used for Pump II.

RECOMMENDATION FOR GASKET SELECTION PUMP II

HANDLING	
PUMP II	GASKET ⑥
Sewer	01-45410 1-0.15
Closed fresh water system	01-45401 1-0.40
Recd marked	

HANDLING	
PUMP I	GASKET ⑥
Sewer	01-45410 1-0.15
Closed fresh water system	01-45401 1-0.40

13	1	Gasket	Packning	01-45410 (lev. separat)
13	1	Gasket	Packning	01-45284 (lev. separat)
12	2	Pin	Stift	01-42400
11	12	Screw	Skruv	05-04-176
10	1	Screw	Skruv	05-04-124
9	1	Screw	Skruv	05-04-115
8	2	Lip seal	Läpplåtning	05-29-139
7	1	Bushing	Bussning	01-45207-3
6	1	Gasket	Packning	See table
5	1	End cover	Lock	01-42388-2
4	1	Impeller	Impeller	08-810B
3	1	Cam	Kam	01-42389
2	1	Shaft	Axel	01-45313
1	1	Body	Pumphus	01-24122-2
Pos.	Qty.	Description	Beskrivning	Material Dimension Drawing no.

This drawing is the property of Johnson Pump AB. It is not to be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of Johnson Pump AB.

Detta ritning är egendomen för Johnson Pump AB. Den får inte kopieras, lagras i ett informationsbibliotek eller spridas på något sätt, elektroniskt, mekaniskt, fotografiskt, ljudinspelning, eller på annat sätt, utan tillstånd från Johnson Pump AB.

Johnson Pump AB  
 Östergatan 10  
 S-114 22 Stockholm, Sweden  
 Tel: +46 8 730 00 00

Johnson Impellerpump  
 Typ F4B-9 Cooling/Cooling

Rev. 1/1  
 Date 2.11.1971  
 Scale 1:1  
 Drawing no. 10-24144